

Brand New Generator Sets Powered by Cummins Diesel Engines										
Line	HS Genset Model	Cummins Engine Model	Rating: 50Hz, 1500 RPM		Rating: 60Hz, 1800 RPM		Approximate Dimension			
			Prime kW / kVA	Standby kW / kVA	Prime kW / kVA	Standby kW / kVA	Length mm	Width mm	Height mm	Weight mm
1	HS30B	4B3.9G	30/38	33/41	34/43	40/50	1980	735	1140	660
2	HS40B	4BT3.9G-1	37/47	40/50	46/58	50/63	1980	735	1140	690
3	HS48B	4BT3.9G-2	48/60	50/63	55/69	60/75	1980	735	1140	785
4	HS66B	6BT5.9G-1	66/83	72/90	73/91	80/100	2240	735	1140	870
5	HS80B	6BT5.9G-1	80/100	88/110	91/114	100/125	2240	735	1140	960
6	HS100C	6CT8.3G	100/125	110/138	155/144	125/156	2650	860	1140	1360
7	HS140C	6CTA8.3G	140/175	158/198	155/194	175/219	2650	860	1290	1400
8	HS227L	LTA10G-1			227/284	250/313	3280	995	1450	2655
9	HS180L	LTA10G-2	180/225	200/250	200/250	225/280	3280	995	1450	2655
10	HS200L	LTA10G-3	200/250	220/275			3280	990	1450	2655
11	HS180N	NT855G-4	180/225	200/250	210/263	230/279	3270	990	1500	2650
12	HS200N	NT855G-5	200/250	220/275	227/284	250/313	3270	990	1500	2650
13	HS240N	NT855G-6	240/300	264/330	250/313	275/344	3270	990	1500	2750
14	HS250N	NTA855G-2	250/312	275/344	275/344	300/375	3270	990	1500	2750
15	HS318N	NTA855G-3			318/398	350/438	3270	990	1500	2750
16	HS280N	NTA855G-4	280/350	310/388			3500	990	1500	2750
17	HS300K	KTA19G-2	300/375	330/413	350/438	400/500	3500	1250	1730	3575
18	HS360K	KTA19G-3	360/450	400/500	410/513	450/563	3500	1250	1730	3668
19	HS400K	KTA28G-4	400/500	440/550	455/569	500/625	3500	1250	1730	3668
20	HS500K	VTA28G-5	500/625	550/688	550/688	600/750	3900	1450	2050	5766
21	HS575Q	QST30G-1	575/719	640/800	680/850	750/938	4570	1780	2218	7416
22	HS600Q	QST30G-2	600/750	660/825	725/907	800/1000	4570	1780	2218	7872
23	HS740K	KTA38G-3	740/925	828/1035	820/1025	900/1125	4880	1900	2550	8149
24	HS900K	KTA38G-4			900/1125	1000/1250	4880	1900	2550	9120
25	HS800K	KTA38G-5	800/1000	880/1000			4880	1900	2550	9116
26	HS810K	KTA50G-1	810/1013	900/1125	900/1125	1000/1250	5900	1900	2550	9180
27	HS910K	KTA50G-2			910/1138	1100/1375	5900	1900	2550	9825
28	HS1000K	KTA50G-3	1010/1250	1120/1400	1100/1375	1250/1563	5900	1900	2550	10016
29	HS1010K	KTA50G-4	1010/1263	1200/1500	1350/1688		5900	1900	2550	10016
30	HS1100K	KTTA50G-2	1100/1375	1280/1600	1250/1563	1500/1875	5900	1900	2550	10020